PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline All Fleet Multi 20W40

PRODUCT DESCRIPTION

Valvoline All Fleet Multi 20W40 has been formulated from highly refined lube base stocks and carefully selected additive packages comprising of antioxidant, detergent / dispersant and anti-wear. The incorporation of these additives provides better engine durability and longer life.

Valvoline All Fleet Multi 20W40 provides ease of engine starting.

Valvoline All Fleet Multi 20W40 is recommended for use in high speed naturally aspirated and turbocharged diesel engines operating at low speed and high torque conditions prevalent in prolonged city stop-&-go, on-&off highway driving conditions including service in hilly regions.

APPLICATION

Valvoline All Fleet Multi 20W40 is recommended for use in all makes of HCVs, LCVs, tractors and gensets.

TYPICAL CHARACTERSTICS

 Kinematic Viscosity, cSt @ 100°C
 14.5

 Viscosity Index
 110

 Flash Point, COC, °C, Min.
 220

 Pour Point, °C, max.
 -21

 TBN, mg KOH/g (ASTM D – 2896)
 8.0

Available Pack: Consult Your Valvoline Representative.

11/2022



Valvoline Cummins Pvt. Ltd. A Joint Venture Company of Valvoline International Inc., USA & Cummins India Ltd. 3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003 Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299 Visit us at: www.valvolinecummins.com

PERFORMANCE

API CH-4

