PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline All Fleet Turbo Synth 15W-40

PRODUCT DESCRIPTION

Valvoline All Fleet Turbo Synth 15W40 is advanced heavy-duty diesel engine oil, formulated with highly stable premium base stocks and specially developed additives and synthetic boosters. Synthetic technology will resist oil thickening for a much longer time and even under extreme operating conditions, it resists molecular tear or breakdown.

The well-balanced formulation incorporating of synthetic technology for Valvoline All Fleet Turbo Synth 15W-40 ensures molecular uniformity resulting in enhanced chemical stability of oil and durability of the all engine components.

Special additives with premium base oil ensures thermal and oxidation stability at severe operating conditions. It provides all round protection to the engine and to the delicate Turbo Charger resulting in enhanced engine life.

APPLICATIONS

It is recommended for all commercial vehicles including new generation HCV's and LCV's plying at long haul.

It is also recommended for MUV's, high horse power tractors and construction & mining equipments.

PERFORMANCE STANDARDS

API CH-4

ADVANTAGES

- Very high thermo-oxidative stability
- Excellent TBN retention
- Ensures excellent soot control / less sludge formation
- Lesser top-ups
- Enhanced rust & wear protection

TYPICAL CHARACTERSTICS

Kinematic Viscosity, cSt @ 40°C	110.1
Kinematic Viscosity, cSt @ 100°C	14.5
Viscosity Index	134
Pour Point, °C	-33
TBN, mg KOH/g (ASTM 2896)	9.2
Flash Point, COC, °C, Min.	220

Available Packs: Consult Your Valvoline Representative.

11/2020



