

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Racing 2T

PRODUCT DESCRIPTION

Valvoline Racing 2T contains high tech additives in a polymer reinforced mineral base oil, designed to keep engines operating at peak efficiency. It has been specially formulated to meet stringent Japanese Specification JASO M 345: FC for lower exhaust smoke and is environmental friendly.

Valvoline Racing 2T prevents spark plug fouling and carbon deposits under most severe operating conditions thus maintaining full power of two-stroke engine.

SELF MIXING PROPERTIES

It contains a special diluent to assist easy mixing and is recommended for use in both pre-mixing and oil injection systems.

APPLICATION

Valvoline Racing 2T has been specially developed to cater to the need of 2-stroke engines of Scooters, Motorcycles and Mopeds of all makes.

Recommended dosage for premixing is 20 ml. Per liter of petrol.

PERFORMANCE STANDARDS

JASO FC

PERFORMANCE BENEFITS

- Low smoke emission rating.
- Exceptionally high engine & spark plug cleanliness.
- Controls combustion chamber deposits thus preventing pre-ignition.
- Prolonged engine life.
- Prevents exhaust system blocking.
- Excellent miscibility with the fuel.

TYPICAL CHARACTERISTICS

Colour	Green
Kinematic Viscosity, @ 40°C, cSt	42.32
Kinematic Viscosity, @ 100°C, cSt	7.2
Viscosity Index	129
Flash Point, COC; °C	110

Available Packs: Consult Your Valvoline Representative.

3/2018



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.

3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

