

---

# PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

---

## Valvoline XLD 20W40

### PRODUCT DESCRIPTION

Valvoline XLD 20W40 is manufactured from highly refined base oils and fortified with additives which provide an excellent oxidation and thermal stability, high detergency, antiwear and anti-corrosion properties.

The use of Valvoline XLD 20W40 will lead to:

- Lower operating cost
- Longer engine life

The use of Valvoline XLD 20W40 provides ease in cold starting and is ideally suited for use in cold as well as hot seasons.

### APPLICATION

Valvoline XLD 20W40 is recommended for use in LCVs & HCVs. Also, recommended for tractors and gensets having both turbo & naturally aspirated diesel engines.

### PERFORMANCE STANDARDS

API CF-4

---

### TYPICAL CHARACTERISTICS

Kinematic Viscosity @ 40°C cSt	128.6
Kinematic Viscosity @ 100°C cSt	14.6
Viscosity Index	110
Flash Point, COC, °C, Min.	220
Pour Point, °C, max	-21
TBN, mg KOH/g	8.1

---

**Available Packs:** Consult Your Valvoline Representative.

11/2022



Valvoline Cummins Pvt. Ltd.  
A Joint Venture Company of  
Valvoline International Inc., USA  
& Cummins India Ltd.  
3<sup>rd</sup> Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003  
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299  
Visit us at: [www.valvolinecummins.com](http://www.valvolinecummins.com)

